



Specifications

- 200A maximum current, 120A 100% (230V)
- **140A maximum current, 100A 100% (110V)**
- Auto line, 110V to 230V +/- 15% (**mono - 50/60hz**)
- 7.5 inches color touch screen Interface
- Auto calculation for program setting through diameter, thickness, configuration and material
- Programs from 1 to 20 levels
- Step modes advance speed-wire pulse
- Dual Gas control: purge gas (through purge time, as well as electrode gas, through pre-gas, or ppm levels)
- Compatible with oxygen measuring systems
- USB software updates (evolution of versions)
- USB program storage: 200 programs per stick
- Possibility of remote through iPad, iPhone or Android
- Detachable cooling unit
- Printing: programs and real parameters
- Data acquisition
- Multi-language: 14 languages programmed
- Compatible with other manufacturer's welding heads
- Wi-Fi Version available (remote control)
- Manual torch available as an option
- **Weight: 46 lb (21 kg) without cooling.**



QUALITY

Dual Gas monitoring at the power source.
Purge gas control through time or ppm level

SIMPLICITY

7.5 inches color touch screen for an intuitive and easy operation

CONNECTIVITY

Remote through your iPhone, iPad or Android (Wi-Fi versions only)
Download the application and access the full touch screen function on your cell phone or tablet

PRODUCTIVITY

Separate cooling unit, 750W, to be plugged on the SAXX-200

Accessories



Welding Heads

