FX360XL Cross-Linc Enabled

Rugged Multi-Process Power Source for Maximum Flexibility









Simple

- Streamlined operator panel minimizes setup time
- Plug in to any 380-600V 3 phase power
- Easy process selection

Reliable

- Built on industry proven design elements of other popular Lincoln Electric welders
- Components designed to run cool for long life in high temperature environments
- Fully encapsulated and environmentally protected electronics
- Engineered for outdoor use and harsh environments (IP23 rated)

Flexible

- Compatible with across-the-arc or CrossLinc™ feeders
- Premium multi-process arc characteristics work with all DC wire, stick and TIG processes
- Choice of models to fit any application and budget
- Lightweight and portable

CrossLinc™ Technology

- Full functionality without control cables
- Enables remote procedure setting at the feeder to improve weld quality
- · Increase arc time with fewer trips to the power source to adjust settings
- Improves safety by reducing jobsite clutter



Processes

Stick, Flux-Cored, MIG, TIG, Gouging

Output

















Applications

- General Fabrication
- Structural
- Power Generation
- Shipbuilding
- Offshore
- Pipeline

Product Highlights

- Desert Duty Rated[™] for extreme temperatures up to 55°C
- VRD® Voltage Reduction Device reduces Open Circuit Voltage for added safety
- Offered in 4 and 6 pack rack configurations
- · Wide 5-425 amperage range
- Capable of Arc Gouging with 1/4 in. (6.4 mm) carbons

Key Accessories

- K4326-1 LN-25X CrossLinc wire feeder
- Other across-the-arc wire feeders without Cross-Linc capability
- · 3-pin Remote Output Control
- · Other Cross-Linc compatible accessories
- MIG Cart
- 4 Pak, 6 Pak, 8 Pak
 Multi-Operator Systems

FX360XL Specifications

Product	Input	Rated Output	Input Current	Output	Dimensions	Weight
Number	Power	Current /Voltage/Duty Cycle	@Rated Output	Range	HxWxL in (mm)	lbs (kg)
K4275-1 (construction) (Across-the-Arc, CrossLinc)	380/460/575/3/50/60	350A/34V/60%	24/22/22	5-425 A	17 x 13 x 23 [421 x 338 x 582]	77 (34.9)





